

# High Speed Bandsaws

**aew delford**  
systems



**AEW Delford Systems** are widely recognised as the leader in high speed, precision bandsaws for the food industry. With over 50 years experience, AEW Delford Systems bandsaws are found in quality food processing facilities world-wide. Most models are available in left and right hand construction, fitted with fixed, half-sliding, full-sliding or roller top tables. Innovative design ensures that our bandsaws can be easily integrated into conveyor and boning lines without sacrificing performance or reliability. Higher blade speeds and increased motor power mean that our smaller machines can deliver improved cutting yields, accuracy, hygiene and operator safety.

## **350**

For butchers' shops, supermarkets, high volume retail and general processing applications.

## **400**

For high volume meat and fish processors, larger retail and catering butchers where accurate portioning is required.

## Features and Benefits

### 350

- Available with fixed or half sliding table.
- Powerful direct drive motor with flexible coupling for minimal maintenance.
- Easily visible eye level control with red 'power on' indicator.
- Available in left or right hand configuration.
- Fast action, precision controlled portion thickness plate with quick release mechanism.

### 400

- Available with fixed, half sliding or full sliding table.
- Available in left or right hand configuration.
- Optional 'drop-in' table conversion quickly converts half sliding table to fixed table configuration.
- Easily visible eye level controls with red 'power on' indicator.
- Option of 2.2kW or 3kW drive gives increased choice of applications.
- Powerful direct drive motor with flexible coupling for minimal maintenance.
- Large sealed for life bearings for minimal maintenance.
- Fast action, precision controlled portion thickness plate with quick release mechanism.



# High Speed Bandsaws

**aw delford**  
systems

## 350 – Technical Specifications – mm (ins)

Table size (fixed)	810 x 660	(31 3/4 x 26)
Table size sliding (fixed half)	911 x 385	(35 3/4 x 15)
Table size sliding (moving half)	450 x 330	(17 3/4 x 12 3/4)
Moving half travel	451	(17 1/2)
Cutting height (max)	320	(12 1/2)
Cutting width (max)	345	(13 1/2)
Overall height	1705	(67)
Floor area (doors closed)	990 x 720	(39 x 28)
Floor to table	910	(35 3/4)
Blade length	2578	(101 1/2)
Blade width	13	(1/2)
Blade speed	27m/sec	(5300 ft/min)
Drive (standard)	1.5kW	(2HP) 1ph or 3ph brake
Electrical supply	200–575v/50–60Hz	
Approx nett weight	142kg	(313lbs)

## 400 – Technical Specifications – mm (ins)

Table size (fixed)	1056 x 885	(41 1/2 x 34 3/4)
Table size sliding (fixed half)	1056 x 402	(41 1/2 x 15 3/4)
Table size sliding (moving half)	645 x 485	(25 x 19)
	645 x 406	(25 x 16) optional
Moving half travel	585	(24)
Cutting height (max)	410	(16 1/8)
Cutting width (max)	407	(16)
Overall height	1920	(75)
Floor area (doors closed)	1020 x 1155	(40 x 45 1/2)
Floor to table	926	(36 1/2)
Blade length	3150	(124)
Blade width	16	(5/8)
Blade speed	32m/sec	(6100 ft/min)
Drive (standard)	2.2kW	(3HP) 3ph brake
Drive (optional)	3kW	(4HP) 3ph brake
Electrical supply	200–575v/3ph/50–60Hz	
Approx nett weight	250kg	(551lbs)

Distributor

## EFFICIENT OPERATION

High blade running speeds result in cleaner cuts without bone chips or splinters. Our blade guidance system and 'turn-to-stop' automatic blade tensioning allows the use of thinner saw blades producing higher cutting yields. Blade changes are faster, without the need for removal of table-tops or guides.

## HEAVY DUTY CONSTRUCTION

Precision castings form the main frame of every AEW Delford Systems bandsaw. All doors, tables, and structural components are made from heavy gauge, high quality stainless steels. Drive wheels are precision machined, nickel plated and balanced to ensure quiet, vibration free running on high quality bearings, and driven by powerful TEFC motors.

## HYGIENE

Our unique main frame construction provides an easy to clean, flat plate frame. The top wheel, tensioner assembly, blade guides and scrapers are all easily removed and replaced in a matter of minutes.

## ENHANCED SAFETY

Eye level controls, safety switches on top and bottom door guards, integral automatic drive motor brakes, and foot operated emergency stop switches increase safety, and low vibration levels significantly reduce operator fatigue.

AEW Delford Systems machines carry CE certification.

AEW THURNE Ltd  
Pinetrees Road, Norwich  
NR7 9BB, UK  
Tel: +44 (0) 1603 700755  
Fax: +44 (0) 1603 700844  
E-mail:  
norwich@awdelford.com

AEW THURNE Inc.  
1.148 Ensell Road,  
Lake Zurich, IL 60047, USA  
Tel: 847 726 8000  
Fax: 847 726 1600  
E-mail:  
chicago@awdelford.com

[www.awdelford.com](http://www.awdelford.com)

SLICE • PORTION • WEIGH • GRADE • LOAD • SEAL • LABEL • SLEEVE