Rebuilding the Food Processing Industry

Viscosity Batter Mixer



gatures

Stainless steel construction with US standard fasteners, bearings, sprockets, belting, and shafts.

Stainless steel viscosity pump and motor with direct drive.

- 1/2 HP mixer.
- 60,000 BTU rated cooling jacket.
- 2000 pounds per hour mixing capacity.
- Level control system to ensure proper amounts of batter at all times.
- Refrigerated sleeve to maintain acceptable temperatures for batter mix.
- Easy access for maintenance
- Mopper capacity of 100 pounds
- Temperature monitoring in mix tank.
- Simple start-up sequence for more consistent and quicker start-ups.
- Shutdown feature that reduces batter waste.
- Easy shutdown system to minimize waste.
- Easy to clean, reducing food safety issues
- Sanitary stainless steel water piping



ABJ Warranty Policy

ABJ Equipfix will repair or replace any ABJ manufactured component that fails due to defect in material or workmanship within 12 months from shipment.

*All OEM parts covered by individual warranties.

THE MOST IMPORTANT PART OF A COATING SYSTEM IS THE ACCURACY OF THE BATTER MIXING. ABJ'S TOTAL VISCOSITY CONTROL MIXER ALLOWS PROCESSORS TO EXCEED THEIR QUALITY AS WELL AS YIELD EXPECTATIONS.