



STS AL - ALC

Automatic L-Sealer

SHRINK TECH SYSTEMS



Features:

- * PLC Controlled
- * Solid Seal Blades with Rounded Corner
- * Adjustable Pin Perf for Air Evacuation
- * Guarding with Safety Switches
- * Horizontal & Vertical Eyes Standard
- * Laser Cut Steel Frame with Durable Powder Coating
- * Quick Change Over with Easy Adjustments
- * Automatic Scrap Wind-up System
- * Available with Closing Conveyor & Var. Speed

Specifications:

Machine Size:	70"l x 39"w x 62"h
Package Size:	L (4" - 17 3/4")
	W (2 3/8" - 13 3/4")
	H (1/8" - 4 3/4")
Seal Bar Size	22" x 18"

Max. Film Width	23.5"
Conveyor Speed	AL 78 FPM
	ALC 0-82 FPM

Power Requirements	220v / 1 PH / 15 AMPS
Air Requirements	90 PSI

www.shrinktechsystems.com



STS 1609-3 Shrink Tunnel

SHRINK TECH SYSTEMS



Features:

- * PID Temperature Control
- * Variable Speed Live Roller Conveyor.
- * Variable Speed Air Control
- * Teflon Mesh Rollers on Conveyor
- * Heat Guards for Operator Protection
- * High Efficiency Heating Tubes.
- * Convection Air Heating System.

Specifications:

Machine Size:	47"l x 26"w x 51"h
Package Size:	W (Max. 14.5") H (Max. 9")
Chamber Size	39"l x 16"w x 9"h
Max.Conveyor Speed	98 FPM
Power Requirements	220v / 3 PH / 28 AMPS

www.shrinktechsystems.com

1226 AMBASSADOR BLVD. ST. LOUIS MISSOURI 63132

PHONE: 314.997.4259 FAX: 314.995.7006