AUTOMATIC HYDRAULIC PISTON FILLER/STUFFER




Market Leader in the Global Food Industry



FPT30e

All in One:

- Filler/Stuffer
- Portioner
- Twister/Linker



Quick product changeover without waste.









All digital:

Using advanced IO-Link internal communications for precise portioning.





At work




- Various assistance systems help the user to find the most efficient way to the desired product.
- Intuitive calibrating system to produce exact weight portions in relation to density of the product.
- Nozzle adjustable twisting, manual casing hold.
- · Clear visual indication of remaining product.
- Counters for batch/total number and weight.

Filling mechnics

- 3 working modes: straight fill, portion and twist.
- Single or continuous operation, programable number of portions for automatic stop.
- Portions from 5 g up to 25 kg, very precise: only ± 1 g.
- Very fast, can produce up to hundreds of portions per minute.
- Number of nozzle twist adjustable from 1-15 revs.
- Programable fill break.

All stainless steel frame

- Very robust construction.
- Completely stainless: entire frame, external and internal, in AISI304, as well as all possible hardware and components.
- Polished surfaces without corners, with CE radius to facilitate cleaning and comply with hygiene standards.
- Double sealed waterproof access panels.
- Closed machine bottom.
- Adjustable, stainless steel machine feet, non-slip and vibration absorbing.





External communications

- Industry 4.0 digital solutions for maintenance, process integration and custom solutions.
- Remote Service and Support access over secure internet connection. (router/ethernet cable or mobile phone)

Hydraulics, electrics and electronics

- Powerful motor, high hydraulic pressure, for the densest or coldest products.
- Hydraulic/electric components of first brands Hydac Germany and Schneider Electric.



innovating automation

- Temperature controlled oil cooling system.
- Easy access to electric panel.
- Very reliable and precise electronic internal digital communications using advanced new I/O Link industry standard components Balluff Germany brand. **BALLUFF**





Software

- Control panel with large 15" Schneider Electric digital touch screen, all information displayed simultaneously and in large size.
- Extensive information on controls, alarms, errors, diagnostics.
- Very advanced and practical software with numerous options. Intuitive, easy to use.
- Interactive recipes, can be stored and executed directly on the machine's screen.





Large 15" touch screen.



Optional: curved nozzle to fill cans/jars.



Optional: 4 swivel casters with brake.

118cm 46.5"

84cm 33"

Technical specifications FPT30e Litres 30 Barrel capacity Gallon Meat capacity ± 25 kg lbs ± 55 Power kW 2.2 HP 3.0 Max. consumption 7.5 400/380 V Α 12.1 230/220 V Α ± 374 Machine net weight kg lbs ± 825 **Packaging** Dimensions (wooden crate) 90x70x130 cm 36"x28"x52" Inch Volume 0.82 m^3


STANDARD DELIVERY

Gross weight

5 nozzles, ext. Ø 14, 20, 30, 38 and 43 mm.

• Hydraulic oil • Piston extraction wrench.

Dimensions



Talsabell s.a. Valencia - Spain www.talsanet.com



± 470

 $\pm 1,035$

kg

lbs













61cm 24"

94cm 37" 121cm 47.5"

Dimensions and illustrations are not binding. We reserve the right to make changes.